

# XYZ PROTURNS RLX 1630

**Swing Over Bed: 400mm**  
**Distance Between Centres: 760mm**  
**Spindle Bore: 54mm**  
**Spindle: 2,500 rpm**



Specification	XYZ RLX 1630
Swing Over Bed	400mm
Swing in Gap	N/A
Gap in front of Faceplate	N/A
Swing over Cross Slide	218mm
Cross Slide Travel	216mm
Distance between Centres	760mm
Maximum Cutting Length	760mm
Spindle Bore	54mm
Spindle Nose	DI-6 Camlock
Spindle Taper	MT4 in bush
Spindle	5.75kW (7.5hp)
Spindle Speeds	150 - 2,500 rpm
Speed Ranges	Single Range 150 - 2,500 rpm
Tailstock Travel	127mm
Tailstock Taper	MT4
Tailstock Diameter	60mm
Bed Width	320mm
Machine Weight	1,550kg
Footprint	2,090 x 1,200 x 1,800mm

## Standard Equipment

- 200mm 3 Jaw Chuck.
- Constant Surface Speed.
- TRAKing®.
- Single Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- Centres and Bushes.

## Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- DXF File Converter.
- Offline Programming.
- Adjustable Backstop.
- Faceplates, Steadies, Chucks and Collet Chucks.
- 4 Station Auto Indexing Toolpost.



Part of the **XYZ Catalogue 2024/25** which includes:  
**ProtoTRAK® Lathes.**  
**Turning Centres.**  
**XL Extra Large Lathes.**  
**Oil Country Lathes.**  
**Manual Mills & Lathes.**  
**Grinders.**  
**Tooling & Accessories.**



Visit [www.xyzmachinetools.com](http://www.xyzmachinetools.com) or  
our YouTube channel to see the video.