

XYZ PROTURNS RLX 355

Swing Over Bed: 360mm
Distance Between Centres: 1,000mm
Spindle Bore: 52mm
Spindle: 4,000 rpm



Specification	XYZ RLX 355
Swing Over Bed	360mm
Swing in Gap	N/A
Gap in front of Faceplate	N/A
Swing over Cross Slide	225mm
Cross Slide Travel	185mm
Distance between Centres	1,000mm
Maximum Cutting Length	900mm
Spindle Bore	52mm
Spindle Nose	D1-6 Camlock
Spindle Taper	MT4 in bush
Spindle	5.75kW (7.5hp)
Spindle Speeds	50 - 4,000 rpm
Speed Ranges	2 Ranges (50 - 1,410 & 100 - 4,000 rpm)
Tailstock Travel	150mm
Tailstock Taper	MT4
Tailstock Diameter	60mm
Bed Width	300mm
Machine Weight	1,955kg
Footprint	2,320 x 1,410 x 1,940mm



Part of the XYZ Catalogue 2024/25 which includes:
ProtoTRAK® Lathes.
Turning Centres.
XL Extra Large Lathes.
Oil Country Lathes.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.

Standard Equipment

- 200mm 3 Jaw Chuck.
- Constant Surface Speed.
- TRAKing®.
- 2 Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Air Assist Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- Centres and Bushes.

Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- DXF File Converter.
- Offline Programming.
- Drilling Attachment.
- Adjustable Backstop.
- Faceplates, Steadies, Chucks and Collet Chucks.
- 4 or 8 Station Auto Indexing Toolpost.
- Swarf Conveyor.



Visit www.xyzmachinetools.com or
 our YouTube channel to see the video.